

CLAIMS

1. A voice storage system comprising:

a circuit switched network for performing communication by circuit

5 switching;

a first telephone which is connected to said circuit switched
network and performs voice communication;

an exchange which is connected to said circuit switched network
and performs voice switching;

10 one or a plurality of private telephones which are connected to
said exchange and perform voice communication; and

a voice storage apparatus which is connected to said exchange,
stores voice in at least speech communication recording by voice data and
an external message transmitted from said exchange, and establishes
15 synchronization between said voice data and said external message
transmitted from said exchange, thereby controlling storage of speech
communication voice.

2. An exchange of a voice storage system,

20 said voice storage system comprising:

a circuit switched network for performing communication by circuit
switching;

a first telephone which is connected to said circuit switched
network and performs voice communication;

25 an exchange which is connected to said circuit switched network

10030963 011500

and performs voice switching;

one or a plurality of private telephones which are connected to
said exchange and perform voice communication; and

a voice storage apparatus which is connected to said exchange,
5 stores voice in at least speech communication recording by voice data and
an external message transmitted from said exchange, and establishes
synchronization between said voice data and said external message
transmitted from said exchange, thereby controlling storage of speech
communication voice,

10 said exchange comprising:

network communicating means for performing connection with
said circuit switched network;

circuit switching means for performing circuit connection between
said circuit switched networks or terminals;

15 terminal communicating means for performing connection
between said exchange and one or a plurality of said private telephones;

entire exchange controlling means for controlling said entire
exchange;

20 exchange time stamp generating means for generating a time
stamp;

exchange voice data controlling means for acquiring said time
stamp from said exchange time stamp generating means, imparting said
time stamp to voice data obtained from said circuit switching means, and
generating said voice data;

25 exchange external message controlling means for acquiring said

10030969.011501

time stamp from said exchange time stamp generating means, imparting
said time stamp to an event obtained from said entire exchange controlling
means, and generating an external message; and

voice storage apparatus communicating means for performing
5 communication with said voice storage apparatus.

3. A voice storage apparatus of a voice storage system,
said voice storage system comprising:

a circuit switched network for performing communication by circuit
10 switching;

a first telephone which is connected to said circuit switched
network and performs voice communication;

an exchange which is connected to said circuit switched network
and performs voice switching;

15 one or a plurality of private telephones which are connected to
said exchange and perform voice communication; and

said voice storage apparatus which is connected to said
exchange, stores voice in at least speech communication recording by voice
data and an external message transmitted from said exchange, and
20 establishes synchronization between said voice data and said external
message transmitted from said exchange, thereby controlling storage of
speech communication voice,

said voice storage apparatus comprising:

exchange communicating means for receiving said external
25 message and said voice data transmitted from said exchange;

10030969-011502

storage apparatus external message controlling means for performing control for fetching said received external message;

storage apparatus voice data controlling means for controlling said received voice data;

5 storage apparatus time stamp acquiring means for acquiring said time stamps from said external message and said voice data;

entire voice storage apparatus controlling means for establishing synchronization of said event by said private telephone obtained from said external message and said speech communication voice obtained from said voice data and controlling said entire voice storage apparatus; and

10 storage apparatus voice storing means for storing said speech communication voice.

4. The voice storage apparatus according to claim 3, wherein
15 hold and transfer events are obtained from said external message by said storage apparatus external message controlling means, voice is obtained from said voice data by said storage apparatus voice data controlling means, said event and said speech communication voice are synchronized with each other by said entire storage apparatus controlling means based on said
20 time stamp obtained by said storage apparatus time stamp acquiring means, and the recording operation is started, paused, restarted or terminated based on a time of a predetermined operation such as hold or transfer.

5. A voice storage system comprising:
25 a circuit switched network for performing communication by circuit

10030969-0150E

switching;

a first telephone which is connected to said circuit switched network and performs voice communication;

an exchange which is connected to said circuit switched network
5 and performs voice switching; and

a voice storage apparatus which is connected to said exchange, and changes reproduced voice by voice data and an external message transmitted from said exchange,

wherein reproduced voice is changed when said exchange
10 establishes synchronization between said voice data and said external message.

6. An exchange of a voice storage system,
said voice storage system comprising:

a circuit switched network for performing communication by circuit
15 switching;

a first telephone which is connected to said circuit switched network and performs voice communication;

an exchange which is connected to said circuit switched network
20 and performs voice switching; and

a voice storage apparatus which is connected to said exchange, and changes reproduced voice by voice data and an external message transmitted from said exchange,

reproduced voice being changed when said exchange
25 establishes synchronization between said voice data and said external data,

10030965-011506

said exchange comprising:

network communicating means for performing connection with
said circuit switched network;

circuit switching means for performing circuit connection between
5 said circuit switched networks or terminals;

terminal communicating means for performing connection
between said exchange and one or a plurality of private telephones;

entire exchange controlling means for controlling said entire
exchange;

10 exchange voice data controlling means for controlling voice data
obtained from said circuit switching means and said voice data transmitted
from said voice storage apparatus;

exchange DTMF detection/analysis controlling means for
detecting/analyzing DTMF information from said voice data obtained from
15 said circuit switching means and converting said information into key
information;

exchange external message controlling means for generating at
least an external message from an event obtained from said entire exchange
controlling means and said key information obtained from said exchange
20 DTMF detection/analysis controlling means;

exchange time stamp acquiring means for acquiring time stamps
from said voice data and said external message transmitted from said voice
storage apparatus;

exchange voice storing means for storing reproduced voice from
25 said voice data controlled by said entire exchange controlling means based

10030969.01502

on control information and a time stamp obtained from said external message; and

voice storage apparatus communicating means for performing communication with said voice storage apparatus.

5

7. A voice storage apparatus of a voice storage system, said voice storage system comprising:

said voice storage system comprising:

a circuit switched network for performing communication by circuit

10 switching;

a first telephone which is connected to said circuit switched network and performs voice communication;

an exchange which is connected to said circuit switched network and performs voice switching; and

15 said voice storage apparatus which is connected to said exchange, and changes reproduced voice by voice data and an external message transmitted from said exchange,

reproduced voice being changed when said exchange establishes synchronization between said voice data and said external data,

20 said voice storage apparatus comprising:

exchange communicating means for receiving said external message and said voice data transmitted from said exchange;

storage apparatus external message controlling means for generating at least an external message to be transmitted to said exchange;

25 storage apparatus voice data controlling means for controlling

10030969-01502

reproduced voice to be transmitted to said exchange;

storage apparatus time stamp generating means for generating
said time stamp;

entire voice storage apparatus controlling means for controlling
5 said entire voice storage apparatus; and

storage apparatus voice storing means for storing reproduced
voice to be transmitted to said exchange.

8. A voice storage system comprising:

10 a circuit switched network for performing communication by circuit
switching;

a first telephone which is connected to said circuit switched
network and performs voice communication;

an exchange which is connected to said circuit switched network
15 and performs voice switching; and

a voice storage apparatus which is connected to said exchange,
and changes reproduced voice by voice data and an external message
transmitted from said exchange,

wherein said exchange comprises:

20 a reproduced voice buffer for temporarily storing said reproduced
voice to be transmitted to said circuit switched network; and

buffer clearing means for clearing unnecessary voice from said
reproduced voice buffer based on a clearing request transmitted from said
voice storage apparatus for changing said reproduced voice.

25

10030969-011502

9. A voice storage apparatus of a voice storage system,
said voice storage system comprising:
a circuit switched network for performing communication by circuit
switching;

5 a first telephone which is connected to said circuit switched
network and performs voice communication;

an exchange which is connected to said circuit switched network
and performs voice switching; and

10 a voice storage apparatus which is connected to said exchange,
and changes reproduced voice by voice data and an external message
transmitted from said exchange,

said exchange comprising:

a reproduced voice buffer for temporarily storing said reproduced
voice to be transmitted to said circuit switched network; and

15 buffer clearing means for clearing unnecessary voice from said
reproduced voice buffer based on a clearing request transmitted from said
voice storage apparatus for changing said reproduced voice,

wherein said voice storage apparatus comprises:

20 buffer clearing means which transmits changed reproduced voice
to said exchange together with said clearing request and clears from said
reproduced voice buffer reproduced voice having a time stamp preceding a
time stamp imparted to said clearing request.

25 10. A voice storage apparatus of a voice storage system,
said voice storage system comprising:

a circuit switched network for performing communication by circuit switching;

a first telephone which is connected to said circuit switched network and performs voice communication;

5 an exchange which is connected to said circuit switched network and performs voice switching; and

said voice storage apparatus which is connected to said exchange, and changes reproduced voice by voice data and an external message transmitted from said exchange,

10 said exchange comprising:

a reproduced voice buffer for temporarily storing said reproduced voice to be transmitted to said circuit switched network; and

buffer clearing means for clearing unnecessary voice from said reproduced voice buffer based on a clearing request transmitted from said voice storage apparatus for changing said reproduced voice,

15 wherein said voice storage apparatus comprises buffer clearing means which transmits said clearing request to said exchange and clears all of reproduced voice remaining in said reproduced voice buffer, and is configured to transmit changed reproduced voice to said exchange upon
20 receiving a notification of termination of clearing said reproduced voice buffer.

11. An exchange of a voice storage system,

said voice storage system comprising:

a circuit switched network for performing communication by circuit
25 switching;

10030969-011502
205770-6960E001

a first telephone which is connected to said circuit switched network and performs voice communication;

an exchange which is connected to said circuit switched network and performs voice switching; and

5 a voice storage apparatus which is connected to said exchange, and changes reproduced voice by voice data and an external message transmitted from said exchange,

said exchange comprising:

10 a reproduced voice buffer for temporarily storing said reproduced voice to be transmitted to said circuit switched network; and

buffer clearing means for clearing unnecessary voice from said reproduced voice buffer based on a clearing request transmitted from said voice storage apparatus for changing said reproduced voice,

15 wherein, besides said reproduced voice buffer and said buffer clearing means, said exchange further comprises:

network communicating means for performing connection with said circuit switched network;

circuit switching means for performing circuit connection between said circuit switched networks or terminals;

20 terminal communicating means for performing connection between said exchange and a private telephone;

entire exchange controlling means for controlling said entire exchange;

25 exchange voice data controlling means for controlling voice data obtained from said circuit switching means and said voice data transmitted

10030969.01502

from said voice storage apparatus;

exchange DTMF detecting means for detecting DTMF information
from said voice data obtained from said circuit switching means and
converting said detected information into key information;

5 exchange external message controlling means for generating at
least an external message from an event obtained from said entire exchange
controlling means and key information obtained from said exchange DTMF
detecting means; and

voice storage apparatus communicating means for performing
10 communication with said voice storage apparatus.

12. A voice storage apparatus of a voice storage system,
said voice storage system comprising:

a circuit switched network for performing communication by circuit
15 switching;

a first telephone which is connected to said circuit switched
network and performs voice communication;

an exchange which is connected to said circuit switched network
and performs voice switching; and

20 said voice storage apparatus which is connected to said
exchange, and changes reproduced voice by voice data and an external
message transmitted from said exchange,

said exchange comprising:

a reproduced voice buffer for temporarily storing said reproduced
25 voice to be transmitted to said circuit switched network; and

10030969.011502

buffer clearing means for clearing unnecessary voice from said reproduced voice buffer based on a clearing request transmitted from said voice storage apparatus for changing said reproduced voice,

wherein said voice storage apparatus comprises:

5 exchange communicating means for receiving said external message and said voice data transmitted from said exchange, and storage apparatus external message controlling means for generating at least an external message to be transmitted to said exchange;

10 storage apparatus voice data controlling means for controlling reproduced voice to be transmitted to said exchange;

entire voice storage apparatus controlling means for controlling said entire voice storage apparatus; and

15 storage apparatus voice storing means for storing reproduced voice to be transmitted to said exchange.

13. A voice storage system comprising:

a circuit switched network for performing communication by circuit switching;

20 a first telephone which is connected to said circuit switched network and performs voice communication;

an exchange which is connected to said circuit switched network and performs voice switching; and

25 a voice storage apparatus which is connected to said exchange, and changes reproduced voice by voice data and an external message transmitted from said exchange,

wherein said voice storage apparatus transmits a part of the whole voice which can be a next reproduction candidate during transmission of said voice data, and said exchange stores said part of the whole voice which can be a next reproduction candidate concurrently with voice reproduction, reproduces a part of said voice which has been already stored when changing said reproduced voice, and subsequently reproduces voice transmitted from said voice storage apparatus after changing said reproduced voice.

10 14. The voice storage system according to claim 13, wherein said part of the whole voice is transmitted, and said exchange stores said part of the whole voice and reproduces a part of said voice which has been already stored when changing said reproduced voice.

15 15. The voice storage system according to claim 14, wherein, when changing said reproduced voice, said exchange is configured to identify voice which should be reproduced from said part of said whole voice.

20 16. The voice storage system according to claim 14, wherein, when changing said reproduced voice, a part of voice which should be reproduced is indicated to said exchange, and said exchange is configured to reproduce said indicated part of said voice.

25 17. An exchange of a voice storage system, said voice storage system comprising:

10030969-014502

a circuit switched network for performing communication by circuit switching;

a first telephone which is connected to said circuit switched network and performs voice communication;

5 said exchange which is connected to said circuit switched network and performs voice switching; and

 a voice storage apparatus which is connected to said exchange, and changes reproduced voice by voice data and an external message transmitted from said exchange, said voice storage apparatus being
10 configured to transmit a part of the whole voice which can be a next reproduction candidate during transmission of said voice data, said exchange being configured to store said part of the whole voice which can be a next reproduction candidate concurrently with voice reproduction, reproduce a part of said voice which has been already stored when changing
15 said reproduced voice and subsequently reproduce voice transmitted from said voice storage apparatus after changing said reproduced voice,

 wherein said exchange comprises:

 network communicating means for performing connection with said circuit switched network;

20 circuit switching means for performing circuit connection between said circuit switched networks or terminals;

 terminal communicating means for performing connection between said exchange and one or a plurality of private telephones;

 entire exchange controlling means for controlling said entire
25 exchange;

10030969-011501

exchange voice data controlling means for controlling voice data obtained from said circuit switching means and said voice data transmitted by said voice storage apparatus;

5 exchange DTMF detection/analysis controlling means for detecting/analyzing DTMF information from said voice data obtained from said circuit switching means and converting it into key information;

10 exchange external message controlling means for generating at least an external message from an event obtained from said entire exchange controlling means and said key information obtained by said exchange DTMF detection/analysis controlling means;

exchange reproduction candidate controlling means for controlling data of a part of the whole voice which has been transmitted from said voice storage apparatus and can be a next reproduction; and

15 exchange voice storing means for storing reproduced voice obtained from said voice data controlled by said entire exchange controlling means based on said external message information and simultaneously storing data of said part of the whole voice which has been transmitted from said exchange reproduction candidate controlling means and can be a next reproduction candidate.

20

18. A voice storage apparatus of a voice storage system, said voice storage system comprising:

a circuit switched network for performing communication by circuit switching;

25 a first telephone which is connected to said circuit switched

40020959.011503

network and performs voice communication;

an exchange which is connected to said circuit switched network and performs voice switching; and

- said voice storage apparatus which is connected to said
- 5 exchange, and changes reproduced voice by voice data and an external message transmitted from said exchange, said voice storage apparatus being configured to transmit a part of the whole voice which can be a next reproduction candidate during transmission of said voice data, said
- 10 exchange being configured to store said part of the whole voice which can be a next reproduction candidate concurrently with voice reproduction, reproduce a part of said voice which has been already stored when changing said reproduced voice and subsequently reproduce voice transmitted from said voice storage apparatus after changing said reproduced voice,
- wherein said voice storage apparatus comprises:
- 15 exchange communicating means for receiving said external message and said voice data transmitted from said exchange;
- storage apparatus external message controlling means for generating at least an external message to be transmitted to said exchange;
- storage apparatus voice data controlling means for controlling
- 20 reproduced voice to be transmitted to said exchange;
- entire voice storage apparatus controlling means for controlling said entire voice storage apparatus;
- storage apparatus voice storing means for storing reproduced voice to be transmitted to said exchange; and
- 25 storage apparatus reproduction candidate controlling means for

1003096-0150

using said storage apparatus voice storing means to acquire a part the whole voice which can be a next reproduction candidate based on current voice data which is being transmitted by said exchange communicating means and transmit it to said exchange.

5

19. The voice storage system according to claim 13, wherein said exchange is configured to reproduce voice transmitted from said voice storage apparatus following reproduction of said part of the voice which has been already stored based on a time stamp imparted to said part of said voice and a time stamp imparted to voice transmitted from said voice storage apparatus after changing reproduced voice.

10

20. An exchange of a voice storage system,

said voice storage system comprising:

15

a circuit switched network for performing communication by circuit switching;

a first telephone which is connected to said circuit switched network and performs voice communication;

20

said exchange which is connected to said circuit switched network and performs voice switching; and

25

a voice storage apparatus which is connected to said exchange, and changes reproduced voice by voice data and an external message transmitted from said exchange, said voice storage apparatus being configured to transmit a part of the whole voice which can be a next reproduction candidate during transmission of said voice data, said

exchange being configured to store said part of the whole voice which can
be a next reproduction candidate concurrently with voice reproduction,
reproduce a part of said voice which has been already stored when changing
said reproduced voice and subsequently reproduce voice transmitted from
5 said voice storage apparatus after changing said reproduced voice, said
exchange being configured to perform reproduction of voice transmitted from
said voice storage apparatus following reproduction of said part of the voice
which has been already stored based on a time stamp imparted to said part
of the voice and a time stamp imparted to said voice transmitted from said
10 voice storage apparatus after changing said reproduced voice,
wherein said exchange comprises:
network communicating means for performing connection with
said circuit switched network;
circuit switching means for performing circuit connection between
15 said circuit switched network or terminals;
terminal communicating means for performing connection
between said exchange and a private telephone;
entire exchange controlling means for controlling said entire
exchange;
20 exchange voice data controlling means for controlling voice data
obtained from said circuit switching means and said voice data transmitted
by said voice storage apparatus;
exchange DTMF detecting means for detecting DTMF information
from said voice data obtained from said circuit switching means and
25 converting it into key information;

10030969 "01150"

exchange external message controlling means for generating at least an external message from an event obtained from said entire exchange controlling means and said key information obtained by said exchange DTMF detecting means;

5 exchange reproduction candidate controlling means for controlling a part of the whole voice which has been transmitted from said voice storage apparatus and can be a next reproduction candidate;

exchange voice storing means for storing said voice data and simultaneously storing said part of the whole voice which has been
10 transmitted from said exchange reproduction candidate controlling means and can be a next reproduction candidate;

exchange time stamp acquiring means for acquiring time stamps from said voice data and a part of changed voice; and

exchange reproduction candidate reproducing means for
15 reproducing said part of said changed voice.

21. A voice storage apparatus of a voice storage system,
said voice storage system comprising:

a circuit switched network for performing communication by circuit
20 switching;

a first telephone which is connected to said circuit switched network and performs voice communication;

an exchange which is connected to said circuit switched network and performs voice switching; and

25 said voice storage apparatus which is connected to said

205110"6960001

exchange, and changes reproduced voice by voice data and an external message transmitted from said exchange, said voice storage apparatus being configured to transmit a part of the whole voice which can be a next reproduction candidate during transmission of said voice data, said

5 exchange being configured to store said part of the whole voice which can be a next reproduction candidate concurrently with voice reproduction, reproduce a part of said voice which has been already stored when changing said reproduced voice and subsequently reproduce voice transmitted from said voice storage apparatus after changing said reproduced voice, said

10 exchange being configured to perform reproduction of voice transmitted from said voice storage apparatus following reproduction of said part of the voice which has been already stored based on a time stamp imparted to said part of the voice and a time stamp imparted to said voice transmitted from said voice storage apparatus after changing said reproduced voice,

15 wherein said voice storage apparatus comprises:

exchange communicating means for receiving said external message and said voice data transmitted from said exchange;

storage apparatus external message controlling means for generating at least an external message to be transmitted to said exchange;

20 storage apparatus voice data controlling means for controlling reproduced voice to be transmitted to said exchange;

storage apparatus time stamp generating means for generating said time stamp;

entire voice storage apparatus controlling means for controlling

25 said entire voice storage apparatus;

10030969-014502

storage apparatus voice storing means for storing reproduced voice to be transmitted to said exchange; and

- storage apparatus reproduction candidate controlling means for using said storage apparatus voice storing means to acquire a part of the
- 5 whole voice which can be a next transmission candidate based on current voice data which is being transmitted by said exchange communicating means and transmitting it to said exchange.

10030969.014502